

JAVAD



TRIUMPH-1M

The new TRIUMPH-1M receiver inherits the best features of our famous TRIUMPH-1. Based on our new 864 channel chip, equipped with the internal 4G/LTE/3G card, easy accessible microSD and microSIM cards, includes “Lift & Tilt” technology.

TRIUMPH-1M

Main Features*

- Total 864 All-In-View Channels
- GPS L1/L2/L2C/L5
- GLONASS L1/L2
- Update Rate 5Hz
- RTK Rate 5Hz
- Memory 256 MB
- RAIM
- Code Differential Base/Rover
- Advanced Multipath Reduction
- MinPad Interface
- Two RS232 Serial Ports (460.8 kbps)
- USB port
- Internal GNSS antenna
- Bluetooth® Interface
- Wi-Fi (IEEE 802.11b/g)
- KFK WAAS/EGNOS (SBAS)
- Rechargeable Li-Ion Battery

Optional Feature

- Galileo E1/E5A
- Galileo E5B
- GLONASS L3
- QSZZ
- Beidou B1
- Beidou B2
- Update Rate 10Hz, 20Hz, 50Hz & 100Hz
- RTK Rate 10Hz, 20Hz, 50Hz & 100Hz
- Data Recording up to 16 GB
- Heading Determination
- GLONASS .2mm Dynamic Calibration
- In-Band Interference Rejection
- JAVAD ArcPad Extension
- 1 PPS timing strobe
- Event Marker
- Lift & Tilt
- Integrated Inclinometers
- Integrated Compass
- Internal 4G LTE Mini Card
- Internal Radio Modem
- Ethernet
- External GNSS Antenna TNC Female connector

Tracking Specification	
Signals tracked	GPS C/A, P1, P2, L2C (L+M), L5 (I+Q); Galileo E1 (B+C), E5A (I+Q), E5B (I+Q), AltBoc; GLONASS C/A, L2C, P1, P2, L3 (I+Q); QZSS C/A, L1C(I+Q), L2C (L+M), L5 (I+Q), SAIF; Beidou B1, B2; SBAS L1, L5
Performance Specifications	
Autonomous	<2 m
Static, Fast Static Accuracy	Horizontal: 0.3 cm + 0.1 ppm * base_line_length** Vertical: 0.35 cm + 0.4 ppm * base_line_length
Kinematic Accuracy	Horizontal: 1 cm + 1 ppm * base_line_length Vertical: 1.5 cm + 1 ppm * base_line_length
RTK (OTF) Accuracy	Horizontal: 1 cm + 1 ppm * base_line_length Vertical: 1.5 cm + 1 ppm * base_line_length
DGPS Accuracy	< 0.25 m post processing; < 0.5 m real-time
Cold / Warm start/ Reacquisition	<35 seconds/ <5 seconds/<1 second
Power Specification	
Battery	Two internal Li-Ion batteries (7.2 V, 5.9 Ah each) with internal charger
Operation Time	Up to 18 hours
Input Voltage	+10 to +30 volts
GNSS Antenna Specifications	
GNSS Antenna Type	Integrated Microstrip (Zero Centered)
Ground Plane	Antenna on a flat ground plane
I/O	
Communication Ports	2x serial (RS232) up to 460.8 kbps; High speed USB 2.0 device port (480 Mbps); Full-duplex 10BASE-T/100BASE-TX Ethernet port; Wi-Fi (IEEE 802.11b/g); Bluetooth V2.0+EDR Class 2 supporting SPP Slave Profile
External Power port	1 port
Radio Specifications	
4G LTE Mini Card	LTE, HSPA+, HSDPA, HSUPA, WCDMA, GSM, GPRS, EDGE (up to 100 Mbps) LTE, EV-DO, 1xRTT CDMA (up to 100 Mbps)
MicroSIM card slot	User accessible, fully sealed
Radio Modem	Internal 406-470MHz UHF radio Internal 902-928/ 868-870 MHz ISM radio (optional)
Base Power Output	1 Watt
Memory & Recording	
Internal Memory	Up to 16 GB of on-board non-removable memory for data storage
SD card slot	High Capacity microSD Card (microSDHC) up to 32GB Class 10; user accessible, fully sealed
Raw Data Recording	Up to 100 times per second (100Hz)
Real Time Data	
Input/Output	JPS, RTCM SC104 v. 2.x and 3.x, CMR
Output	NMEA 0183 v. 2.x and 3.0, BINEX
Status Indicator	Six LEDs, two function keys (MinPad)
Environmental Specifications	
Enclosure	Molded magnesium alloy and plastic, waterproof IP67
Operating /Storage Temperature	-40° C to +60° / -45° C to +85° C ***
Humidity	100% condensing
Shock	Survives a 2 m drop onto hard surface
Dimensions	7 x 3.78 x 7 in (178 x 96 x 178 mm)
Weight	3.75 lbs (1.7 kg)/4.02 lbs (1.82 kg) with modem antenna

* For the full list of standard and optional features see www.javad.com

** For good observation conditions and proper length of observation session

*** The operating temperature range of Li-Ion batteries is -30° C to +55°
The storage temperature of Li-Ion batteries is -20° C to +45°

Specifications are subject to change without notice



JAVAD GNSS
www.javad.com

Rev.1.2 November 28, 2014