

Victor-4 Pro

Android / Windows Tablet



Key Features

- Multi-Touch WXGA (1280 x 800)
- Android 11 / Windows 10
- Snapdragon™ Octa-Core / Intel N4200
- Wi-Fi 802.11 a/b/g/n/ac, 2.4 & 5 GHz
- Bluetooth 5.0
- microSD
- 4G LTE
- 16 MP Camera

The Victor-4 Pro is a rugged mobile tablet with Android 11 or Windows 10 OS for data collection with JAVAD GNSS receivers. Paired with the JAVAD Mobile Tools or Field Survey applications, the Victor-4 Pro configures the GNSS receiver for RTK, and records real time positions, annotations and raw data. The sunlight viewable touch screen, camera, cell modem, Bluetooth and Wi-Fi, make the Victor-4 Pro a sturdy and reliable tablet for GNSS surveys.

VICTOR-4 Pro Specifications



System	Operating System	Android 11 / Windows 10 Q
	Processor	Qualcomm® Snapdragon™ Octa-core Kryo™ 260 / Quad-core Intel® Pentium N4200
	Memory	6 GB LPDDR4, 64 GB eMMC / 8 GB LPDDR4, 128 or 256 GB
	Display	Multi-Touch Screen, Dragontrail™ High Ion-Exchange Cover Glass 1280*800 WXGA IPS LCD
	GPU	Qualcomm® Adreno™ 512 GPU / Intel® HD Graphics
	GPS (optional)	Qualcomm SDR660 GNSS receiver
	Camera	Rear: 16 MP, Front 2 MP
Sensors	Ambient light sensor, Compass, Accelerometer, Gyroscope	
Communications	Cellular (optional)	4G LTE Snapdragon X12 LTE / AirPrime EM7455 or EM7430
	Wi-Fi	802.11 a/b/g/n/ac, 2.4 GHz and 5 GHz
	Bluetooth	Long-range Bluetooth®, v5.0 + EDR, Class 1.5, BLE support
	USB	USB-C, USB 3.1 OTG x 1 / USB 3.0 x 1
	External Interfaces	Optional RS-232 9-Pin D-Sub connector with 5V DC or 12V DC power output Dock connector (Pwr, USB 2.0, & HDMI) / Dock connector (Pwr, USB 2.0, HDMI, & Ethernet
	Audio	3.5 mm audio jack
	Keypad	Adjustable LED backlit keys, Four-way directional navpad, Home key, Power key, Enter key, User-programmable function keys, OEM configurable/customizable
Power	Power Input	12V DC power input jack
	Battery	Li-Ion 43.2 Whr, removable, rechargeable, field changeable
	Operation Time	10 - 12 hours
	Extended Operation	Optional 21.6 Whr for hot swap, 5 - 6 hours
Physical & Environmental	Operating Temperature	- 20°C to +50°C
	Storage Temperature	- 30°C to +70°C
	Humidity	95% non-condensing
	Dimensions (mm)	228 x 145 x 16.5
	Weight (g)	630 g with battery
	Sealing	IP68
	Drop	1.5 m multi-drop resistance to concrete
Regulatory	FCC, CE, RoHS 2, EN62368 Safety, Industry Canada	
Peripherals & Accessories	Standard Accessories:	<ul style="list-style-type: none">• Standard removable battery• AC wall charger with international plug kit• Capacitive small-tip stylus w/tether• Quick Start Guide• Hand strap• Connector port dust cover• 2-year warranty

GNSS performance is dependent on signal quality, satellite geometry, ionospheric and tropospheric conditions, baseline length, multipath effects and RF interference. Specifications may be changed without notice.

Janak Positioning & Surveying Systems Pvt. Ltd.

Add: B-28, Sector-4 Noida - 201301

Janak.ji@yahoo.com

9811008317, 1800116009

JANAK

www.janaksurvey.com

